

Phaser® 3435

Black and White Laser Printer

High end features, suitably priced for your business

Our low cost Phaser® 3435 printer offers big business features such as built-in networking, automatic two-sided printing and plenty of expansion options. It's perfect for small businesses and work teams or even as a dedicated personal printer.



Affordable, powerful business printer


- Rapid print speeds (33 ppm A4) keep pace with your growing business.
- Automatic two-sided printing makes it easy to reduce paper use.
- Never wait for pages; fast first page out in as fast as 8.5 seconds (25 seconds from sleep mode).
- Built-in networking helps you connect and print quickly.
- Heavy print volumes? An optional high-capacity print cartridge lets you print up to 10,000 pages per cartridge.

Flexible, space-saving design

- Small footprint helps save precious office space, since the Phaser 3435 takes up very little room on the desk.
- 250-sheet paper tray goes longer between refills; an optional 250-sheet paper tray lets you load an entire ream of paper (500 sheets) at one time.
- Ready for your network with support for Windows, Macintosh and Linux operating systems.

Engineered for quality

- 1200 dpi print resolution and PCL/PostScript support gives you sharp, professional-looking documents.
- Heavy duty; supports big monthly print volumes.
- Handles complex documents without delays, thanks to standard 64 MB memory (expandable to 320 MB).
- One year on-site warranty.



Print
A4
33 ppm

WxDxH:
400 x 433 x 285 mm

Phaser® 3435

Black and white laser printer



		Phaser® 3435DN
Speed		Up to 33 ppm (A4)
Duty Cycle		Up to 80,000 pages / month
Paper Handling	Paper input	Standard Multipurpose Tray: 50 sheets; Custom sizes: 76 x 127 mm to 216 x 356 mm Tray 1: 250 sheets; Sizes: A4, A5, A6
		Optional Tray 2: 250 sheets; Sizes: A4, A5, A6
Paper output		150 sheets face down, 1 sheet face up
Automatic two-sided printing		Standard
Print		
First-page-out-time		As fast as 8.5 seconds
Resolution		Up to 1200 image quality
Processor		400 MHz
Memory (std / max)		64 MB Flash ROM (includes 4 MB for additional fonts and macros) / 320 MB
Connectivity		Parallel, USB 2.0, 10/100Base-TX Ethernet
Page description languages		PostScript® 3™ compatibility, PCL® 6, PCL® 5e, IBM ProPrinter, Epson emulation
Print features		Watermarks, Poster printing, N-up, Fit to page, Reduce/enlarge, Overlays, Booklets, Toner saver
Warranty		One-year on-site warranty

Device Management

Phaser Installer, CentreWare® IS Embedded Web Server, CentreWare Web, Global Print Driver

Print Drivers

Windows® 2000/XP/2003 Server, Vista, Mac OS® version 8.6-9.2, 10.1-10.5, Various Linux® OS including SUSE™ 8.2-9.2, Red Hat® 8-9, Fedora™ Core 1-4, Mandrake 9.2-10.1

Security

802.1x

Font Support

1 bitmap, 45 scalable, 136 PostScript® fonts

Media Handling

Multipurpose Tray: 60 – 163 gsm

Media types: Plain paper, envelopes, transparencies, card stock, postcards

Tray 1 and Tray 2 (optional): 60 – 90 gsm

Media types: Plain paper

Two sided printing: 75 – 90 gsm

Operating Environment

Operating Temperature: 10° to 32° C

Humidity: 20% to 80%

Sound pressure levels:

Printing: 53 dB(A)

Standby: 25 dB(A)

Warm-up time (from sleep mode): Less than 15 seconds

Electrical

Power: 220–240 VAC, 50/60 Hz

Power consumption: Standby: 36 W / 34 W

Printing: 509 W / 526 W

Sleep: 6 W / 7 W

Power save: 11 W

ENERGY STAR® qualified

Dimensions (WxDxH)

401 x 434 x 312 mm

Weight: 12.7 kg

Package dimensions (WxDxH): 501 x 615 x 421 mm

Certifications

Listed UL 60950/CSA C22.2 No. 60950, CE Mark applicable to Directives 2006/95/EC, 2004/108/EC and 99/5/EC

What Comes in the Box

- Phaser 3435 printer
- Print cartridge (4,000 print capacity¹)
- Software and Documentation CD (with User Manual, Quick Installation Guide, Warranty Statement)
- Power cord
- USB cable



Phaser 3435 shown with optional Tray 2

Supplies

Standard-Capacity Print Cartridge¹:

4,000 std pages 106R01414

High-Capacity Print Cartridge¹:

10,000 std. pages 106R01415

¹ Average standard pages. Declared Yield in accordance with ISO/IEC 19752.

Yield will vary based on image, area coverage and print mode.

Options

250-sheet Tray 097N01539

32 MB Memory 097S03132

128 MB Memory 097S03136

256 MB Memory 097S03761

