

Xerox ColorQube™ 9201/9202/9203

Multifunction Printer



Xerox ColorQube 9201
shown with Offset Catch Tray.



Xerox ColorQube 9202
shown with Office Finisher.



Xerox ColorQube 9203
shown with High Volume Finisher with Booklet Maker, Post Process Inserter, Z-Fold/C-Fold unit and High Capacity Feeder.

	Xerox ColorQube 9201	Xerox ColorQube 9202	Xerox ColorQube 9203
Output Speed – Printing and Copying			
Color	High Resolution/Photo Mode: 30 ppm Enhanced Mode (Default): 38 ppm Standard Mode*: 50 ppm Fast Color Mode*: 60 ppm	High Resolution/Photo Mode: 35 ppm Enhanced Mode (Default): 45 ppm Standard Mode*: 60 ppm Fast Color Mode*: 70 ppm	High Resolution/Photo Mode: 38 ppm Enhanced Mode (Default): 50 ppm Standard Mode*: 70 ppm Fast Color Mode*: 85 ppm
Black and white	High Resolution/Photo Mode: 38 ppm Enhanced Mode (Default): 50 ppm Standard Mode*: 70 ppm Fast Color Mode*: 85 ppm		
First-Copy-Out Time – Letter Size/A4, from Platen			
	As fast as 8.1 seconds		
Copy Specifications			
Copying			
Document Scanner	Duplex Automatic Document Feeder (DADF) 100-sheet capacity		
Sides (input:output)	1-1, 1-2, 2-2, 2-1		
Quantity	1 to 9,999		
Resolution (max)	600 x 600 dpi		
Concurrency	Unlimited program-ahead consistent with configuration (Copy, Fax and Scan)		
Memory	1 GB Pre-collation memory, 512 MB, 80 GB Disk minimum		

* Standard and Fast Color speeds are available for printing in PostScript only. Copy settings are limited to High Resolution/Photo and Enhanced Mode speeds.

Xerox ColorQube™ 9201/9202/9203

Basic Copy Features & Options	<p>Collation Automatic 2-sided/Duplex Auto Reduction and Enlargement to fit selected paper size Hole Punching Booklet Creation Stapling Large Job Interrupt Auto Paper Select Authentication for Services (i.e., Color Copy) Auto Tray Switching</p>
Imaging Copy Features	<p>Image Quality:</p> <ul style="list-style-type: none"> • Original Type Selection: Photo & Text, Photo, Text, Newspaper/Magazine, Maps • Original Subtype: Printed original, Photocopied original, Photograph, Inkjet original, Solid ink original • Image Options: Lighten/Darken, Sharpness, Saturation • Image Enhancement: Background Suppression, Contrast • Color Effects: Off, Lively, Bright, Warm, Cool • Color Balance: 7 levels of density for each of Cyan, Magenta, Yellow and Black <p>Book Copying/Bound Copying Edge Erase Single Color Repeat Image Mixed Size Original Image Shift (with Auto Center option) Image Shift Preset: Support for 3 Preset Options Annotation and Bates™ stamping (with color capability)</p>
Output Copy Features	<p>Transparencies Dividers (blank or imaged) Booklet Creation Multi-up (up to 15 columns by 15 rows) Invert Image (negative or mirror image) Covers (Front only, front and back, back only) Build Job: (Enables page-level programming and also lets you proof each section or delete last section as the job is built) Inserts and Tab insertion Sample Set and Job Storage (Store and recall job programming) Heavy weight paper (not rough stock)</p>
Features	<p>Help (Intuitive text and graphic descriptions) Xerox Standard Accounting (Copy, Print, Scan, Fax) Languages: (Select up to 21 languages for user interface – US English, International English, International French, Italian, German, International Spanish, Dutch, Portuguese, Brazilian (Brazilian Portuguese), Swedish, Norwegian, Danish, Finnish, Turkish, Greek, Russian, Czech, Polish, Hungarian, Romanian or Catalan)</p>
Security	<p>IP Filtering for TCP/IP network communications Enable Secure Workflows Audit Log: Provide export capability of log, includes username of log on attempts SNMPv3 Support LUI Job Queue Confidentiality: Requires a PIN to delete a Secure print job Image Overwrite (On-demand/Immediate or Scheduled) Encryption of user jobs stored on hard disk</p>
Reduction/Enlargement	<p>Variable Zoom: 25% – 400% in 1% increments Size: user-programmable percentages (100%, Auto%, 25%, 50%, 64%, 70%, 78%, 94%, 141%, 180%, 200%, 400%)</p>

Xerox ColorQube™ 9201/9202/9203

Foreign Device Interface (FDI) (Optional)	Interface to third party access control devices, coin machines, card readers Validates Metadata Accept Authentication Login at LUI and pass to third party Networking Account Interface with third party accounting terminal for accounting UI MIB Compliance – supports the Finishing MIB Support a variety of vending stations available through the Xerox Custom Application Service
USB Port	PC Interface for upload/download of Xerox Copier Assistant Customer device administration/software upgrade
Accessibility Option	Xerox Copier Assistant (XCA) software provides a PC-based alternative to the user interface touch screen. Used in conjunction with a customer-supplied PC attached via USB port, this software supports text-to-speech, screen magnification and easy PC keyboard access to basic and advanced copy features
Paper Handling – Duplex Automatic Document Handler	
Capacity	100 sheets
Speed	75 images per minute (ipm) black-and-white, 51 ipm color
Paper Sizes Sensed	5.5 x 8.5 in. to 11 x 17 in. SEF or 5.5 x 8.5 in. to 8.5 x 11 in. LEF (A5/148 x 210 mm to A3/297 x 420 mm SEF or A5/148 x 210 mm to A4/210 x 297 mm) LEF
Weights	13 lb bond to 43 lb bond (50 to 160 gsm)
Paper Handling – Three Front Loading Paper Trays – Paper Trays 1, 2 and 3	
Capacity	Trays 1 & 2: 550 sheets of 20 lb bond (75 gsm) each tray Tray 3: 2,100 sheets of 20 lb bond (75 gsm)
Sizes	Trays 1 & 2: 5.5 x 8.5 in. SEF to 11 x 17 in. SEF (A5/148 x 210 mm to A3/297 x 420 mm) Tray 3: 8.5 x 11 in. LEF (A4/210 x 297 mm)
Weights	16 lb bond to 57 lb bond/80 lb cover (60 to 220 gsm)
Types	Trays 1 & 2: Plain Labels Carbonless Punched paper Tray 3: Plain Carbonless Punched paper
Paper Handling – Bypass Tray (Tray 4)	
Capacity	100 sheets of 20 lb bond (75 gsm)
Sizes	A5/8.5 x 5.5 in./#10 Envelope SEF to SRA3/12 x 18 in. SEF
Weights	16 lb bond to 80 lb cover (60 to 220 gsm)
Types	Plain Heavy weight Extra heavy weight Labels Transparencies (paper backed not supported) Envelopes Carbonless Punched paper Glossy

Xerox ColorQube™ 9201/9202/9203

Paper Handling – High Capacity Feeder (Tray 5)			
Capacity	Up to 4,000 sheets of 20 lb bond (75 gsm)		
Sizes	8.5 x 11 in. (A4/210 x 297 mm) LEF Optional 8.5 x 11 in./8.5 x 14 in. Short Edge Kit – 8.5 x 14 in. (A4/210 x 297 mm) SEF with 2,000 sheet capacity Optional 11 x 17 in. Short Edge Kit – 11 x 17 in. (A3/297 x 420 mm) SEF with 2,000 sheet capacity		
Weights	16 lb bond to 57 lb bond/80 lb cover (60 to 220 gsm)		
Paper Handling – Total Capacity			
Device Total Capacity	7,300 sheets		
Output Option – Offsetting Catch Tray (OCT) Option			
Capacity	500 sheets of 20 lb bond (75 gsm)		
Output Option – Office Finisher Option			
Capacity ¹	Top Tray – 250 sheets Stacking Tray – 2,000 sheets		
Sizes	5.5 x 8.5 in. (A5/148 x 210 mm) to 11 x 17 in. (A3/297 x 420 mm)		
Weights	16 lb to 57 lb bond/80 lb cover (60 to 220 gsm)		
Stapling ¹	50 sheets Single and dual		
Hole Punch (Optional)	<table border="0"> <tr> <td>North America 3-hole punch 2-hole Legal punch</td> <td>Europe 2-hole punch 4-hole punch 4-hole “Swedish” punch</td> </tr> </table>	North America 3-hole punch 2-hole Legal punch	Europe 2-hole punch 4-hole punch 4-hole “Swedish” punch
North America 3-hole punch 2-hole Legal punch	Europe 2-hole punch 4-hole punch 4-hole “Swedish” punch		
Output Option – High Volume Finisher Option			
Capacity ¹	Top Tray – 250 sheets Stacking Tray – 3,000 sheets		
Sizes	5.5 x 8.5 in. (A5/148 x 210 mm) to 11 x 17 in. (A3/297 x 420 mm)		
Weights	13 lb to 57 lb bond/80 lb cover (60 to 220 gsm)		
Stapling ¹	100 sheets Single (any corner), dual, front, rear, SEF and 4-stitch		
Hole Punch (Optional)	<table border="0"> <tr> <td>North America Option 1 – 3-hole punch Option 2 – 2-hole Legal punch</td> <td>Europe 2-hole punch 4-hole punch and 4-hole “Swedish” punch</td> </tr> </table>	North America Option 1 – 3-hole punch Option 2 – 2-hole Legal punch	Europe 2-hole punch 4-hole punch and 4-hole “Swedish” punch
North America Option 1 – 3-hole punch Option 2 – 2-hole Legal punch	Europe 2-hole punch 4-hole punch and 4-hole “Swedish” punch		
Output Option – High Volume Finisher with Booklet Maker Option			
Capacity ¹	Top Tray – 250 sheets Stacking Tray – 3,000 sheets (2,000 sheets with Z-Fold/C-Fold)		
Sizes	5.5 x 8.5 in. (A5/148 x 210 mm) to 11 x 17 in. (A3/297 x 420 mm)		
Weights	16 lb to 57 lb bond/80 lb cover (60 to 220 gsm)		
Stapling ¹	100 sheets Single (any corner), dual, front, rear, SEF and 4-stitch		

¹ Paper capacities are based on 20 lb/75 gsm stock; capacities will vary with different weight stocks.

Xerox ColorQube™ 9201/9202/9203

Hole Punch (Optional)	North America Option 1 – 3-hole punch Option 2 – 2-hole Legal punch	Europe 2-hole punch 4-hole punch and 4-hole “Swedish” punch
Booklet Maker Capacity¹	Tray stop up: 25 booklets (1-15 sheets per booklet) Tray stop down: Unlimited	
Sizes	Letter – 8.5 x 11 in. (A4/210 x 297 mm) Legal – 8.5 x 14 in. (216 x 356 mm) Ledger – 11 x 17 in. (A3/297 x 420 mm)	
Weights	16 lb to 57 lb bond/80 lb cover (60 to 220 gsm)	
Stapling ¹	Saddle-stitch (2-15 sheets/8-60 page booklet)	
Folding	V-folding (1-15 sheets/unstapled)	
Output Option – Z-Fold/C-Fold Unit with HVF with Booklet Maker Option		
Capacity ¹	50 sheets or unlimited capacity with tray stop in the down position	
Sizes	Letter – 8.5 x 11 in. (A4/210 x 297 mm)	
Weights	16 lb to 32 lb bond (60 to 120 gsm)	
Output Option – Post Process Inserter (optional with HVF and HVF with Booklet Maker)		
Capacity ¹	250 sheets Tray stop down: unlimited	
Sizes	Letter – 8.5 x 11 in. (A4/210 x 297 mm) Legal – 8.5 x 14 in. (216 x 356 mm) Ledger – 11 x 17 in. (A3/297 x 420 mm)	
Weights	16 lb to 57 lb bond/80 lb cover (60 to 220 gsm)	
Output Option – Convenience Stapler		
Capacity	50 sheets 5,000 staples Requires a separate outlet	
Print Specifications		
Network Printing – Simultaneous Rip, Receive, Program Ahead, Queue Processing and Transmit		
Processor	1 GHz	
Memory (ESS)	512 MB	
System Disk	80 GB minimum	
Print Languages (PDL)	PCL 6/PCL 5c emulation PostScript 3 TIFF (6.0 Old JPEG and New JPEG) PDF XPS	
First-Print-Out Time – Letter Size/A4		
	As fast as 7.2 seconds	

¹ Paper capacities are based on 20 lb/75 gsm stock; capacities will vary with different weight stocks.

Network Printing – Printing Features	
	Bi-directional Print Drivers provide device and job status Embedded web server for remote control/monitor/setup Job monitoring at the device and desktop Special font Banner Sheet Rotate Image Offset Support PCL and PS switching Custom Macintosh Driver (Watermark, Booklet Creation, JBA, Secure, Sample, Delay Print) Page Segmentation Save and restore print job settings
Network Printing – Print Driver Options	
Paper Output	Job Type <ul style="list-style-type: none"> • Secure, Sample, Delay, Saved Paper Selection by attribute (including transparency separators) Duplex (2-sided) Finishing <ul style="list-style-type: none"> • Multiple stapling positions • Hole punch • Booklet creation • Fit to new paper size • Saddle stitch with High Volume Finisher with Booklet Maker Output tray selections Store and recall driver setting
Special Pages	Exception page programming (covers, inserts, exception pages)
Image Options	Print Settings (High Resolution/Photo – 600x600 dpi, Enhanced – 450x567 dpi, Standard – 300x500 dpi and Fast Color – 225x450 dpi) Reduction/Enlargement Invert Image (negative/mirror)
Layout/Watermark	N-up (16)/Multi-up Booklet layout/finishing Fit to new paper size Image orientation Watermark option
Print Protocols and Networks	
Physical	Ethernet 10/100/1000BaseT, 10BaseT, 10Base2 (IEEE802.5) (Token ring) – via adapter Wireless Ethernet (IEEE802.11a/b/g) – via third party adapter IPv6 support for printing 802.1x support
Operating Systems	Windows XP, 2000, Server 2003, Server 2008, Server XP 64 bit, Server 2003 64 bit, Server 2008 64 bit, Windows Vista Mac OSX 10.3 & 10.5 HP UX 11/11i AIX Solaris 8/9/10 SPARC Solaris10 x86 Linux x86/x86_64
Network Protocols	TCP/IP, LPR/LPD, Raw IP (Port 9100), NetBIOS SMB, IPX/SPX, IPP, NDPS®/NEPS AppleTalk, Bonjour
Administrative Protocols	DHCP, BOOTP, SNMP, WINS, DDNS, SLP v2, HTTP, RARP

Xerox ColorQube™ 9201/9202/9203

Automated Services Platform	<p>MeterAssistant: automatically collects and securely submits your device meter reads to Xerox using a built-in audit process to increase billing accuracy</p> <p>SuppliesAssistant: proactively manages ink stick supplies and monitors usage to ensure you have the right supplies at the right time</p> <p>Maintenance Assistant: Offers a fast (and free) way to resolve potential issues and receive assistance and automate the troubleshooting/repair process. Diagnostic data is sent to Xerox, allowing for problems to be solved faster with increased uptime.</p>
Xerox CentreWare® Internet Services	Allows simple remote installation setting of configuration options and management of the device
Xerox CentreWare® Web	<p>A web-based server application for network administrators that permits web browser-based device management from any workstation, whether running Windows, UNIX or any other operating system:</p> <ul style="list-style-type: none"> • Works with any SNMP-managed printer from any manufacturer • Provides help with device discovery and installation, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management • Requires Windows XP, Vista, Server 2003, Server 2008 and Internet Explorer 6.0 and higher
Novell NDPS/NEPS	Server gateway application: centralized management tool
Xerox CentreWare® for Unicenter TNG®	Provides added identification to the general discovery performed by Unicenter TNG and the ability to see the ColorQube® under a Unicenter TNG Business Process View
Xerox CentreWare for Tivoli® NetView®	Provides for the identification of Xerox ColorQube®, WorkCentre® and Phaser® printers and multifunction printers in the general discovery performed by Tivoli NetView
Xerox CentreWare for HP® OpenView®	<p>Provides for the identification of Xerox ColorQube®, WorkCentre® and Phaser® printers and multifunction printers in the general discovery performed by HP OpenView</p> <p>Provides traps and message updates to the OpenView alarm browser and the ability to launch CentreWare Internet Services for device management directly from OpenView</p>
Xerox Barcode Pro PS (optional) Information available at www.xeroxofficesapsolutions.com	Enables intelligent PostScript printing on Xerox multifunction printers by storing Xerox software, as well as the barcode fonts on the printer hard disk. Enables the printing of barcodes from any application (SAP R/3 client or mainframe) that supports PostScript printing. Automatically calculates the check digit, places start/stop and middle bar characters in the data string, compresses, encodes and rotates the barcode through 90 or 270 degrees
Xerox Device Types for SAP R/3 Environment Information available at www.xeroxofficesapsolutions.com	<p>Simplifies printing in SAP R/3 environments by providing users of SAP R/3 3.x, 4.x, 4.5x, 4.6x, SAP Enterprise 4.7x, ERP applications with enhanced ColorQube printing functionality (PostScript and PCL):</p> <ul style="list-style-type: none"> • One- to two-sided printing • Finishing provides single or dual stapling • Tray pull location from any tray • # of copies – provides the ability to print multiple copies • Paper Type and color – provides ability to select paper types and colors, such as transparency, red, etc. • Print security via PIN ID capability • Job Based Accounting (JBA) – Provides capability to add JBA UserIDs to SAP print jobs • Printer banner sheet – Provides the ability to enable/disable printer banner sheets • Barcode printing – Xerox standard PostScript device types available at www.xeroxofficesapsolutions.com supports Intelligent Barcode Printing with Xerox Barcode Pro PS. This Barcode Pro PS can be purchased at www.font.net
Xerox SAP R/3 Intelligent Barcode Utility (optional) Information available at www.xeroxofficesapsolutions.com	Provides built-in intelligence that allows the printing of barcodes on any appropriately configured PostScript printer on the SAP R/3 4.1x, 4.5x, 4.6x and within Latin-1 (ISO8859-1) SAP system code pages only. Used in conjunction with Xerox PostScript Device Types for SAP R/3 environment and Xerox Font Center Barcode Fonts. Utility enables automated checksum calculation, placement of start/stop characters, encoding of data string and data compression
CentreWare Internet Services – Integrated Web Pages Provided by the Device	
Device Status	<p>Web server embedded in SMart Controller:</p> <ul style="list-style-type: none"> • Tray status/contents • Consumables status • Alerts
Job Submission	<p>Print ready files: PS, PCL, TIFF, PDF</p> <p>Output feature selection (2-sided, staple, fold, hole punch, paper select)</p> <p>Delivery options (Immediate, proof, delay and secure)</p>

Xerox ColorQube™ 9201/9202/9203

Device Administration	Allows simple, remote installation setting of configuration options and management of the device
Scan Template Management	Support 250 scan templates Create device specific CentreWare scan templates Select confirmation sheet options Share scan templates via device cloning
Browsers (minimum versions)	Netscape 7.x, 9.x Internet Explorer 6.x Safari 3.0 Mozilla Firefox 2.x Opera 9.x Chrome 1.0
Support	Online support available via web page
Scanning	
Concurrency	Scan while the system is printing, copying, or while it is transferring scan to network or fax jobs
Input Speed	Scan at up to 51 ipm color scanning, up to 75 ipm black-and-white – 8.5 x 11 in. LEF (A4/210 x 297 mm) at all resolutions
Resolutions (DPI options)	600 x 600 dpi 400 x 400 dpi 300 x 300 dpi 200 x 200 dpi 200 x 100 dpi 150 x 150 dpi 100 x 100 dpi 72 x 72 dpi
Scan Presets	Archival (Normal Quality - Smallest file size) For Sharing and Printing (Normal Quality - Small file size) For High Quality Printing (High Quality - Large file size) For OCR (High Quality - Large file size) Simple Scan (Normal Quality - Small file size)
Quality/File Size	Normal Quality (Small file size) Higher Quality (Large file size) Maximum Quality (Largest file size)
Maximum Scan Area	11 x 17 in. (A3/297 x 420 mm)
Authentication	Secure device login with network user name and password Supports Kerberos (Windows 2000/UNIX/Windows Server 2003, Windows Server 2008) SMB (Windows NT 4.0/Windows 2000/Windows Server 2003, Windows Server 2008) Novell over IP/IPX (Novell NetWare 4.x/5.x/6.x) Common Access Card (CAC) / Personal Identity Verification (PIV) Xerox Secure Access Unified ID System LDAP PIN-based guest login
File Formats	PDF TIFF Multipage TIFF Searchable PDF PDF/A XPS Searchable XPS Linearized PDF Searchable PDF/A JPEG

File Compression	G3 (photo and halftone photo originals), G4 (text and mixed originals), MRC, JPEG, JBIG2
Scan Features	Mixed sized Original Support for Scan Export Simplified scanning workflow User Interface (IQ, file size, Templates) Scan in Novell IP Build job for Scan to file Auto Detect Color or Black-and-White image data Auto Contrast support for Scan Export – Enable better color and grayscale scanned Image Quality by correcting for different levels of black within a scanned image Scan to Searchable PDF, PDF/A and XPS Scan to Home Scan to Mailbox Store and reprint jobs
Scan to E-mail	
Capability	Scan to e-mail (manual address entry), directory (Exchange/Notes/LDAP) address searching, internal address book or public address book (up to 128 recipients)
Network Protocol	SMTP MIME encoded IPV6
Scan Features	E-mail signatures (6 lines each of 128 character max), e-mail message body (user configurable), e-mail CWIS confirmation sheet options
Network Scanning	
Capability	Enables device-specific network scan workflows (destination templates) to be easily created and edited via CentreWare® Internet Services: <ul style="list-style-type: none"> • Scan to file • Scan to network server/directory • Scan to Windows XP client via Windows Image Acquisition (WIA) or TWAIN driver • Scan to e-mail • Scan to Microsoft Exchange public folders • Scan to PC Desktop
Network Protocol	Novell (NCP via IPX/SPX) FTP Microsoft SMB via TCP/IP HTTP/HTTPS IPV6
Document Management Fields (Metadata)	Features only available in Network Scan to File Templates: <ul style="list-style-type: none"> • 1-6 user programmable metadata fields per network scan to file template and unlimited fields within the template <ul style="list-style-type: none"> – Metadata Field consists of field name, display at the LUI, default value and other configurations • Customized fields viewed on user interface • Variable data entered using virtual keyboard at device
Scan Template Management	Share scan templates among ColorQube via device cloning Scan template management (250 templates) with CentreWare Internet Services Select confirmation sheet option
Scan Features	Build job (for Scan to file only) (enables special programming for different pages in one document – can be used for inserts, mixing input from the document glass and document feeder), duplex scanning, auto detect document size, scan mixed size originals, scan to edge
Network Scanning – Software Solutions	
Supported Scan Destinations - scan template creation (varies by scanning software options purchased)	Scan to application (workflow, Electronic Document Management System/Repositories) Scan to Microsoft Exchange 2000 Web folders Scan to web URL Scan to PC Desktop (SE and Professional editions) Scan to mailbox

Xerox Scan to PC Desktop Professional (optional)	<p>A desktop offering that provides advanced document imaging, archiving, editing and organization tools:</p> <ul style="list-style-type: none"> • Nuance PaperPort Professional image viewing and file management software: <ul style="list-style-type: none"> – Complete PDF functionality – Secure PDF workflow of all scanning applications • Nuance OmniPage Pro Office (for desktop/client installation) – Professional OCR software for digital archiving and document conversion • Image Retriever – provides fully automated retrieval of scanned images direct from a scan enabled Xerox ColorQube to individual desktops. Also includes e-mail inbox polling capability
Xerox SMARTsend® (optional)	<p>Server based document routing software that supports multiple scan-enabled multifunctional systems (up to 250 per server):</p> <ul style="list-style-type: none"> • Enables transformation, distribution and routing of scanned documents – with features like LDAP and auto discovery • Workflow creation via web browser-based task creation (destinations, devices, document attributes – 20 file types including searchable PDF, workflow settings, workflow summary) • Scan to file destinations: e-mail, Novell Netware folder, network folder, SMB folder, FTP, Microsoft Exchange 2000 web folders, web URL, remote printers • Scan to document repository destinations: DocuShare®, Domino, Domino.doc, Microsoft SharePoint • Workflow initiation via device scanning user interface (template selection at device UI)
Xerox SMARTsend Professional (optional)	<p>Everything in Xerox SMARTsend, plus:</p> <ul style="list-style-type: none"> • Workflow initiation via Paperware (Scan cover sheets) • Server-based Optical Character Recognition (OCR) • Adding Metadata • Scan to Internet fax file destination
Fax Specifications	
Fax Features – Internet Fax	
Capability	<p>Direct document transmission to remote Internet fax machines or e-mail clients (SMTP) Reception and automatic printout of documents sent via e-mail from remote Internet fax machines or e-mail clients</p>
Maximum Scan Area	11 x 17 in. (A3/297 x 420 mm)
Authentication	<p>Optional secure device login with network user name and password Supports: Kerberos (Windows 2000/UNIX/Windows Server 2003/Windows Server 2008) SMB (Windows NT 4.0/Windows 2000/Windows Server 2003/Windows Server 2008) Novell over IP/IPX (Novell NetWare 4.x/5.x/6.x) Common Access Card (CAC) / Personal Identity Verification (PIV) Xerox Secure Access Unified ID System Optional PIN-based guest login</p>
Address Directory Access	<p>Corporate address list via LDAPv3 Downloaded address list (comma-separated file format) Internal LDAP or Public address book</p>
File Formats	PDF and Multi TIFF
Resolutions	<p>600 x 600 dpi 400 x 400 dpi 300 x 300 dpi 200 x 200 dpi 200 x 100 dpi 150 x 150 dpi 100 x 100 dpi 72 x 72 dpi</p>
Network Protocols	<p>SMTP POP3 (RFC 1939)</p>
Compliance	<p>ITU-T T.37 Compliant 508 Compliant</p>

Xerox ColorQube™ 9201/9202/9203

Features	Signature (SA configurable – 6 lines each of 128 character max) Delivery Confirmation: <ul style="list-style-type: none"> • Email receipt option • Confirmation reply option Cover sheet option Subject (248 characters) User configurable message body
Fax Features – Network Fax Server Enablement	
Capability	Provides walk-up faxing and hard copy output of received faxes when integrated with fax server applications (Fax server and software must be purchased separately from supplier.). Transmission speeds, number of lines, compatibility and compression are dependent on fax server configuration
Maximum Scan Size	11 x 17 in. (A3/297 x 420 mm)
Authentication	Optional secure device login with network user name and password Supports Kerberos (Windows 2000/UNIX/Windows Server 2003, Windows Server 2008) SMB (Windows NT 4.0/Windows 2000/Windows Server 2003, Windows Server 2008) Novell over IP/IPX (Novell NetWare 4.x/5.x/6.x) Common Access Card (CAC) / Personal Identity Verification (PIV) Xerox Secure Access Unified ID System Optional PIN-based guest login
Network Protocols	Novell (NCP via IPX/SPX) or IP FTP Microsoft SMB via TCP/IP HTTP/HTTPS SMTP
Fax Send Features	One- or two-sided scanning (up to 11 x 17 in. – A3/297 x 420 mm) Phone number entry Add to send list Delay send (specific time) Image quality selection (photo and text, photo, text, lighten/darken, five levels of sharpness)
Fax Print Features	One- or two-sided printing Quantity Staple on/off Collate on/off Secure print on/off Finisher output tray selection (top tray or main tray)
Supported Network Fax Vendors	Multiple vendors, certified by the Xerox Alliance Partner Program. For details visit www.xerox.com
Fax Options – Walk Up Option (one or two line options)	
Compatibility	ITU (CCITT) Group 3
Memory	512 MB
Speed/Modems	1 or 2 V.34 modems: 33,600 bps. Less than 4 seconds per page transmission time. (ITU Doc 1 standard resolution)
Compression/Speed	MH/MR/MMR/JBIG G3/Super G3

Xerox ColorQube™ 9201/9202/9203

Fax Send Features	<p>Quality/Resolution</p> <ul style="list-style-type: none"> • Original type: photo, photo/text, text only • Fax – off platen, mixed sizes or bound/book <p>Audio line monitor Transmission options (report/header) Reduce/Split large documents Cover letter Delayed send Build job (up to 1,000 images) Polling</p>
Fax Receive Features	<p>One- or two-sided printing Stapled or unstapled, hole punch Receive print mode – Manual (size, margin, stock)/Auto Auto answer delay Secure receive Junk fax prevention</p>
Fax Reports	<p>Activity Dial directory Group directory Options Pending jobs Broadcast report</p>
Fax Mailboxes	<p>Up to 100 password-protected mailboxes (one-line option) Up to 200 password-protected mailboxes (two-line option)</p>
Auto Dialing Features	<p>Speed Dials:</p> <ul style="list-style-type: none"> • 200 (one-line option) • 1,000 (two-line option) <p>Group Dials:</p> <ul style="list-style-type: none"> • Up to 100 groups with up to 200 recipients per group (one-line option) • Up to 200 groups with up to 400 recipients per group (two-line option) <p>Auto Redial:</p> <ul style="list-style-type: none"> • Up to 14 attempts • 1 to 25 minute intervals • Batch send (up to memory capacity)
Resolutions	<p>Send: 200 x 100 dpi (Standard) 200 x 200 dpi (Fine) 600 x 600 dpi (Superfine)</p> <p>Receive: 200 x 100 dpi (Standard) 200 x 200 dpi (Fine) 300 x 300 dpi (Superfine) 400 x 400 dpi (Superfine) 600 x 600 dpi (Superfine)</p>
LAN Fax	Send fax directly from print drivers
Accounting Options – Xerox Standard Accounting	
Tracking	Copy, Print, Fax and Scan usage to secure print
Accounting	<p>Up to 2,500 user accounts (User ID) Up to 500 general accounts (Client) Up to 500 group accounts (Department)</p>
Features	<p>Enable/disable via the web UI or the device GUI in tools; administrator can manage the feature remotely Data can be exported via a CSV file; supports entering XSA ID into the print driver when submitting a print job</p>

Xerox ColorQube™ 9201/9202/9203

Accounting Options – Job Based Accounting – Third Party Enablement			
	Enhanced network accounting with up to the minute data on how the ColorQube system is being used; comprehensive management and enterprise scale tracking and reporting of device usage of copy, print, scan and server fax. Various options available through Xerox Alliance Partner solutions. For details visit www.xerox.com Security enhancements with the addition of HTTPS protocol support ColorQube requests account authentication from third party server enabling larger databases of users and accounts		
Machine Specifications			
Monthly Duty Cycle			
	ColorQube 9201: up to 150,000 pages/month ColorQube 9202: 225,000 pages/month ColorQube 9203: 300,000 pages/month		
Average Monthly Print Volumes			
	ColorQube 9201: 15,000 prints ColorQube 9202: 17,000 prints ColorQube 9203: 21,000 prints		
Electrical Requirements			
North America	Voltage : 110 –127 VAC +/- 6 % (99-135 VAC) Frequency: 60 Hz +/- 5 % , 15 A		
Europe	Voltage : 220-240 VAC +/- 6 % (198-254 VAC) Frequency: 50 Hz +/- 6 % , 10 A		
Power Consumption (Base IOT)			
Running (Max)	1410 watts		
Running (Average)	750 watts		
Standby Mode	360 watts		
Low Power Mode	200 watts		
Sleep Mode	113 watts		
Warm-up (Ready to Mark)	From Low Power: 47 sec. From Sleep: 3 min 30 sec. The Intelligent Ready power management feature learns the unique print usage patterns of an office so the device will be in ready mode when needed and automatically go into lower power modes when not needed. This feature maximizes energy efficiency and results in pages being generated in as fast as 8 seconds		
Sound Levels			
Base IOT	Run Continuous	Impulse	Standby
Sound Power Level	7.3 B(A)	7.8 B(A)	5.5 B(A)
Sound Pressure Level	58 dB(A)	63 dB(A)	40 dB(A)
Environmental Considerations			
Required Temperature Range	50° to 90° F (10° to 28° C)		
Required Relative Humidity	5 % to 85 %		

Xerox ColorQube™ 9201/9202/9203

Dimensions and Weight	Width	Depth	Height	Weight
IOT with Offset Catch Tray (OCT)	55 in./1,398 mm	28.4 in./722 mm	45.5 in./1,156 mm	501 lbs./227 kg
IOT with Office Finisher	63 in./1,601 mm	28.4 in./722 mm	45.5 in./1,156 mm	562.2 lbs./255 kg
IOT with High Volume Finisher	82.4 in./2,093 mm	28.4 in./722 mm	45.5 in./1,156 mm	687 lbs./311.5 kg
IOT with High Volume Finisher with Booklet Maker, Post Process Inserter and Z-Fold/C-Fold Unit	96.2 in./2,443 mm	28.4 in./722 mm	45.5 in./1,156 mm	813 lbs./368.8 kg
IOT with OCT and High Capacity Feeder	64 in./1,618 mm	28.4 in./722 mm	45.5 in./1,156 mm	567 lbs./257 kg
Certifications				
	FCC Class A Compliant (U.S.); DOC Class A Compliant (Canada) CB Certified (IEC 60950/EN 60950) 2004/108/EC 2006/95/EC 99/5/EC Submitted for full system Common Criteria (ISO 15408) certification			
Device Specifications				
Xerox Extensible Interface Platform™ (EIP)				
	Xerox Extensible Interface Platform (EIP) is an embedded software platform built with state-of-the-art web technologies. This platform provides the means for software developers to quickly build solutions that are more intuitive and user-friendly for office workers. Chief among the capabilities provided by EIP is the development of tailored applications with customized user interfaces, and card-based authentication solutions supporting a personalized user experience			
Supplies	Description	Order Number		
Cartridge-Free Ink Sticks	4 sticks Black (Sold)	108R00832		
	4 sticks Cyan (Sold)	108R00829		
	4 sticks Magenta (Sold)	108R00830		
	4 sticks Yellow (Sold)	108R00831		
	4 sticks Black (Metered)	108R00836		
	4 sticks Cyan (Metered)	108R00833		
	4 sticks Magenta (Metered)	108R00834		
	4 sticks Yellow (Metered)	108R00835		
Staple Cartridge Staple Refills	Office Finisher	008R12964 008R12941		
50 sheet Cartridge Staple Refills	High Volume Finisher	008R12919 008R12920		

Xerox ColorQube™ 9201 / 9202 / 9203

100 sheet Cartridge Staple Refills	High Volume Finisher	008R12912 008R12898
Staple Refills	Booklet Maker (for HVF)	008R12897
Staple Refills	Convenience Stapler	008R12941
SMart Kits	Description	Order Number
Cleaning Unit		108R00841



©2009 Xerox Corporation. All rights reserved. Xerox®, the sphere of connectivity design, CentreWare®, DocuShare®, SMARTsend®, WorkCentre and ColorQube™ are trademarks of Xerox Corporation in the United States and/or other countries. ENERGY STAR® is a U.S. registered mark. As an ENERGY STAR® Partner, Xerox Corporation has determined that these products meet the ENERGY STAR® guidelines for energy efficiency. Postscript is a registered trademark of Adobe Systems Incorporated in the United States and/or other countries. Other marks are trademarks or registered trademarks of the companies with which they are associated. Product information and/or specifications are subject to change without notice. 05/09 Q925S-01UA