

WorkCentre[®] 7425 / 7428 / 7435 Colour Multifunction Printer



WorkCentre 7425
shown with the Three Tray option.



WorkCentre 7428
shown with High-Capacity Tandem Tray and Office Finisher LX with Booklet Maker options.



WorkCentre 7435
shown with High-Capacity Tandem Tray, High Capacity Feeder and Professional Finisher options.

	WorkCentre 7425	WorkCentre 7428	WorkCentre 7435
Output Speed – Printing and Copying			
Black and white	Up to 25 ppm (pages per minute) A4/210 x 297 mm LEF Up to 16 ppm 216 x 356 mm Up to 14 ppm A3/297 x 420 mm	Up to 28 ppm A4/210 x 297 mm LEF Up to 18 ppm 216 x 356 mm Up to 16 ppm A3/297 x 420 mm	Up to 35 ppm A4/210 x 297 mm LEF Up to 23 ppm 216 x 356 mm Up to 20 ppm A3/297 x 420 mm
Colour	Up to 20 ppm A4/210 x 297 mm Up to 13 ppm 216 x 356 mm Up to 11 ppm A3/297 x 420 mm	Up to 28 ppm A4/210 x 297 mm Up to 18 ppm 216 x 356 mm Up to 16 ppm A3/297 x 420 mm	Up to 35 ppm A4/210 x 297 mm Up to 23 ppm 216 x 356 mm Up to 20 ppm A3/297 x 420 mm
First-Page-Out Time			
Copy – Black and white	As fast as 6.7 seconds	As fast as 5.0 seconds	As fast as 5.0 seconds
Copy – Colour	As fast as 8.7 seconds	As fast as 6.4 seconds	As fast as 6.4 seconds
Paper Handling			
Paper Handling – Duplex Automatic Document Feeder			
Capacity	75 sheets (based on 80 gsm paper)		
Speed	50 images per minute black and white/45 images per minute colour (A4 long edge feed (LEF))		
Sizes	A5/148 x 210 mm to A3/297 x 420 mm		
Weights	60 to 120 gsm		
Paper Handling – Bypass Tray			
Capacity¹	100 sheets		
Sizes	A6/105 x 148 mm to SRA3/320 x 450 mm		
Weights	55 to 256 gsm		
Types	Same as front-loading trays plus envelopes		

¹ Paper capacities are based on 80 gsm stock; capacities will vary with different weight stocks.

Paper Handling – Main Tray 1 (Standard)	
Capacity ¹	520 sheets
Sizes	User adjustable from 139.7 x 182 mm to A3/297 x 420 mm
Weights	60 to 256 gsm
Types	Plain Paper Recycled Bond Custom Type 1 through 5 Lightweight Heavyweight Extra Heavyweight Transparency Gloss Heavyweight Gloss Extra Heavyweight Gloss Labels Punched Letterhead Pre-printed
Envelope Tray (Optional – replaces Tray 1)	
Capacity ¹	Up to 60 envelopes
Sizes	DL, C5, C6
Weights	75 to 90 gsm
Paper Handling – Input Tray Options - Three Tray Option	
Tray 2, Tray 3, Tray 4	520 sheets each
Sizes	User adjustable from 139.7 x 182 mm to SRA3/320 x 450 mm
Weights	60 to 256 gsm
Types	Plain Paper Recycled Bond Custom Type 1 through 5 Lightweight Heavyweight Extra Heavyweight Transparency Gloss Heavyweight Gloss Extra Heavyweight Gloss Labels Punched Letterhead Pre-printed Envelopes
Total Capacity ¹	2,180 sheets (Includes Tray 1, Three Tray option and Bypass Tray)
Paper Handling – Input Tray Options - High-Capacity Tandem Tray Option	
Tray 2	520 sheets
Sizes	User adjustable from 139.7 x 182 mm to SRA3/320 x 450 mm
Tray 3 and Tray 4	2,000 sheets total

¹ Paper capacities are based on 80 gsm stock; capacities will vary with different weight stocks.

WorkCentre 7425 / 7428 / 7435

Sizes	B5, A4
Weights	60 to 256 gsm
Types	Plain Paper Recycled Bond Custom Type 1 through 5 Lightweight Heavyweight Extra Heavyweight Transparency Gloss Heavyweight Gloss Extra Heavyweight Gloss Labels Punched Letterhead Pre-printed Envelopes
Total Capacity¹	3,140 sheets (Includes Tray 1, High-Capacity Tandem Tray option and Bypass Tray)
Paper Handling – High-Capacity Feeder (HCF)	
Capacity	2,000 sheets of 75 gsm
Sizes	A4/210 x 297 mm LEF, 184 x 266.7 mm LEF
Weights	55 to 216 gsm
Total Capacity¹	5,140 sheets with High Capacity Tandem Tray option – 4,180 sheets with Three Tray option
Output – Standard	
Stacking Trays¹	Dual Offset Catch Tray – up to 250 sheets each Face up Tray – up to 100 sheets
Sizes	A5/148 x 210 mm to SRA3/320 x 450 mm
Weights	60 to 256 gsm
Output – Integrated Office Finisher Option	
Stacking Tray	500 sheets of 80 gsm A4 or 250 sheets of 80 gsm A3
Sizes	B5 to A3
Weights	60 to 220 gsm
Stapling	Single Auto stapling (50 sheets maximum less than 90 gsm or 2 sheets of 220 gsm covers) A3, A4, B4 and B5 sizes supported
Output – Office Finisher LX Option	
Stacking Tray	2,000 sheets unstapled or 1,000 sheets single staple or 750 sheets dual staple (90 gsm)
Sizes	B5 to A3
Weights	60 to 220 gsm
Stapling	Single and dual Auto stapling (50 sheets maximum less than 90 gsm) A3, A4, B4 and B5 sizes supported

¹ Paper capacities are based on 80 gsm stock; capacities will vary with different weight stocks.

Output – Optional Hole Punch for Office Finisher LX	
	2-hole punch 4-hole punch
Output – Optional Booklet Maker (Score/Crease, Saddle-stitch Staple) for Office Finisher LX	
Capacity	40 booklets (1-15 sheets per booklet – 80 gsm or less; 2-10 sheets per booklet – over 80 gsm)
Sizes	A4/210 x 297 mm 216 x 356 mm A3/297 x 420 mm
Saddle-stitch Stapling	2-15 sheets / 8 – 60 page booklet 55 to 90 gsm
Score/Crease	1-15 sheets / unstapled
Output – Professional Finisher Option	
Top Tray	500 sheets
Stacking Stapling Tray	1,500 sheets
Sizes	B5 to A3
Weights	60 to 220 gsm
Stapling	Single Auto stapling (50 sheets maximum) – 90 gsm A3, A4, B4 and B5 sizes supported
Booklets - Booklet Tray	Saddle-stitch up to 15 sheets (One 169 gsm cover plus fourteen 90 gsm sheets) V-fold up to 5 sheets A3, A4 supported
Hole Punch	2–4 Hole Punch, Swedish Hole Punch
Copy Specifications	
Document Scanner	Duplex Automatic Document Feeder with 75-sheet capacity (based on 80 gsm paper)
Sides (input:output)	1:1, 1:2, 2:2 and 2:1
Quantity	1 to 999
Resolution	600 x 600 dpi
Concurrency	Concurrent scan, print, fax
Digital Imaging	Enhanced Gloss Level Auto colour Auto rotation Image shift Edge erase Auto centering Original type selection (photo and text, photo, text, map) with subtypes Lighter/darker Background suppression Auto and manual contrast Sharpness Colour balance, colour shift and saturation

Reduction/Enlargement	Variable zoom from 25 % to 400 % in 1 % increments Anamorphic zoom Six user-programmable percentages
Special Features	Auto paper select Auto reduction/enlargement to fit selected paper size Auto registration Auto tray switching Automatic job recovery Auto colour selection Area Designation Poster mode Watermark Secure Watermark (requires Secure Watermark Kit option) Annotation Single/Dual colour Copy calibration Booklet creation Multi-up – 2, 4 or 8 up Repeat Image Transparency dividers Negative image Mirror image Covers insertion (front only, front and back, back only, blank or printed) Build Job (enables special programming for different pages in one document – can be used for inserts, different paper sources and mixing input from the document glass and the document feeder) Store and recall job programming Job interrupt Book copying Sample job Mixed-size originals Hole Punch (requires Professional Finisher or Office Finisher LX) V-Folding (requires Professional Finisher) Saddle-stitch booklets (requires Professional Finisher or Office Finisher LX) Stapling (single/dual/quad) (quad requires Professional Finisher) ID Card Copy
Foreign Device Interface	Interface to third-party access control devices, coin machines and card readers Supports a variety of vending stations available through the Xerox Alliance Partner Programme

Print Specifications

System

Memory	1.5 GB
---------------	--------

System Disk	Minimum 40 GB
--------------------	---------------

Network Printing – Network Controller

Processor	667 MHz
------------------	---------

Printer Languages (auto sensing/switching)	Adobe® Postscript® 3™ (optional) TIFF PCL® 5c PS-PDF: v1.3 PCL® 6 HP-GL2™ XPS®
---	--

Network Printing – Resolution

	Print Engine: 1200 x 2400 dpi
--	-------------------------------

Network Printing – Printing Features	
Features	<p>Enhanced Gloss Level Print Calibration Secure Print Delay Print (specific time) Sample Set Booklet creation Cover selection Inserts and exception pages Store File in Folder Paper selection by attribute N-up Saddle-stitch booklet making (requires Professional Finisher or Office Finisher LX) Hole Punch (requires Professional Finisher or Office Finisher LX) Booklet Fold / V Folding (requires Professional Finisher or Office Finisher LX) Watermark Secure Watermark (requires optional Secure Watermark Kit) Fit to new paper size Transparency Separators Banner Sheet enable/disable Output tray selection Image Quality Draft Mode Store and Recall driver settings Reduce/enlarge Mirror image Margins Bi-Directional status Two sided printing Scaling Overlays Print to Fax (requires optional Fax Kit)</p>
Connectivity	<p>Ethernet 10/100BaseTX High speed USB 2.0 printer port Wireless Ethernet (IEEE 802.11b) via third-party adapters Parallel Port (optional)</p>
Operating Systems	<p>Microsoft® Windows® 2000, XP® 32-bit, XP 64-bit, Windows Server 2003 32-bit, Windows Server 2003 64-bit, Windows Vista 32-bit, Windows Vista 64-bit Mac OS® 10.3 and above AIX 51v5.3 HP UX 11.0, 11i v2 Solaris 8, 9, 10 Linux® FedoraCore 1, 5 RedHat Enterprise Linux 4 SUSE 10.x</p>
Network Protocols	<p>TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6 Netware: Bindery and NDS IPX/SPX, NDPS®/NEPS (with Server Gateway) AppleTalk®: EtherTalk® Microsoft Windows Networking over IP and NetBEUI (All protocols not in use can be disabled)</p>
Administrative Protocols	<p>DHCP, BOOTP, SNMP, WINS, DDNS, SLP® v2, HTTP, RARP, DHCP Autonet, SSL</p>
Fonts	<p>Postscript 3: 136 Type 1 fonts, 2 Multiple Master fonts PCL: 81 scalable fonts, line printer bitmap font</p>

Printer Drivers	Environment	PCL5c and PCL 6	PostScript
Vista XPS (mini driver available)	Windows 2000/2003/XP 32 Bit Windows 2003/XP 64 Bit Windows Vista/Vista 32 Bit Windows Vista/Vista 64 Bit (Microsoft certified)	Bi-directional with user-selectable interface (standard ² and enhanced ³)	Bi-directional with user-selectable interface (standard ² and enhanced ³)
	Macintosh® OS 10.3.0 and above	N/A	Enhanced PPD file
	UNIX	N/A	Bi-directional with Xerox Custom Graphical User Interface
Xerox Mobile Express Driver (X-MED)	<p>Makes it easy for mobile users to find, use and manage Xerox and non-Xerox devices in every new location. Plug into a new network, and X-MED automatically discovers available printers and provides status and capability information. Save a list of “favourite” printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT.</p> <ul style="list-style-type: none"> • Printers are automatically discovered • Printer list can be managed based on location • Gives Bi-directional feedback device status, supplies, queue management 		
Xerox Global Print Driver (X-GPD)	<p>A truly universal print driver that lets IT administrators install, upgrade and manage Xerox and non-Xerox devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.</p> <ul style="list-style-type: none"> • Printers are automatically discovered • Printer list can be managed based on location • Gives Bi-directional feedback device status, supplies, queue management 		
Print Submission Tools	<ul style="list-style-type: none"> • Command prompt LPR/UNIX tool for print submission • Contents Bridge tool supports TIFF/PDF/XPS and Office 2007 direct print 		
Device Management			
Management Support	SNMP Version 1, SNMP Version 2c and Version 3 trap over TCP/IP and IP MIB access (IETF-MIB II RFC 1213), Host Resources MIB RFC 2790, Printer MIB RFC 1759 v. 2		
Xerox CentreWare® Web	<ul style="list-style-type: none"> • A Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system • Works with any SNMP-managed printer from any manufacturer • Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management 		
IP Filter	Allows administrator to control print access to device via IP address.		
Xerox CentreWare® for Unicenter TNG®	<ul style="list-style-type: none"> • Provides added identification to the general discovery performed by Unicenter TNG and the ability to see the device under a Unicenter TNG Business Process View • Provides full integration with event management and the choice to integrate with problem management and advanced Help Desk 		
Xerox CentreWare® for Tivoli® Netware®	<ul style="list-style-type: none"> • Provides for the identification of Xerox N-Series printers and WorkCentre multifunction systems in the general discovery performed by Tivoli NetView • Provides the ability to see the discovered Xerox printers/devices in a Xerox Printers Set in addition to the Printers SmartSet • Provides full integration with the NetView and Event Browser and Tivoli Enterprise Console (TEC) 		
Xerox CentreWare® for Microsoft Management Console (MMC)	CentreWare MC Snap-in supports printer discovery and management via a Microsoft Management Console (MMC) link to an embedded Web server. It is a general-purpose management display framework for hosting administrative tools.		

² Standard: Driver based on Microsoft tree structure user interface (includes Xerox features and functionality)

³ Enhanced: Xerox custom graphical user interface

Xerox CentreWare® for HP® OpenView®	<ul style="list-style-type: none"> • Provides for the identification of Xerox N-Series printers and WorkCentre multifunction devices in the general discovery performed by HP OpenView • Provides the ability to see the current status of discovered Xerox printers/devices under a Xerox PrinterMap and IP Map via colour-coded icons • Provides traps and message updates to the OpenView alarm browser and the ability to launch CentreWare Internet Services for device management directly from OpenView
Xerox Device Manager	<p>Xerox Device Manager collects and manages the data that drives fact-based decisions for your enterprise device management environment. It is a single tool to install print queues and configure, manage, monitor and report on both networked and locally connected devices – regardless of vendor – across your enterprise. Xerox Device Manager provides:</p> <ul style="list-style-type: none"> • Device monitoring and troubleshooting • Extensive reporting and discovery of new devices • Usage collection, chargeback, and billing capabilities
Xerox Device Types for SAP R/3 Environment <i>Information available at www.xeroxofficesap.com</i>	<p>Simplifies printing in SAP R/3 environments by providing users of SAP R/3 v4.6C, 4.x and 3.x ERP applications with enhanced WorkCentre printing functionality (PostScript and PCL):</p> <ul style="list-style-type: none"> • Simplex or duplex printing • Finishing – single or dual stapling • Tray pull location from any tray • Print security via PIN ID capability at the WorkCentre
Xerox SAP R/3 Intelligent Barcode Utility (Optional) <i>Information available at www.xeroxofficesap.com</i>	<p>Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer on the SAP R/3 4.x (or higher) network. Used in conjunction with Xerox Device Types for SAP R/3 Environment and Xerox Font Center Barcode Fonts. Utility automatically calculates checksum, placement of start/stop characters, and encoding of data string Web server embedded on SMart network controller</p> <ul style="list-style-type: none"> • Tray status/contents • Consumables status
Xerox Barcode Pro PS <i>Information available at www.xeroxofficesap.com</i>	<p>Enables intelligent PostScript printing on Xerox multifunction printers by storing Xerox software as well as the barcode fonts on the printer hard disk. Enables the printing of barcodes from any application (client or mainframe) that supports PostScript printing. Automatically calculates the check digit, places start/stop and middle bar characters in the data string, compresses and encodes the data string, and rotates the barcode through 90 or 270 degrees.</p>
Smart eSolutions	
Meter Assistant	<p>Automates the process of collecting and submitting meter reads for tracking and billing of Xerox device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.</p> <p>Device Direct or via client</p>
CentreWare® Internet Services – Integrated Device Web Page	
Device Status	<p>Web server embedded on SMart Network Controller™</p> <ul style="list-style-type: none"> • Tray status/contents • Consumables status
Print Queue Viewing	Complete job print queue management – hold, release, promote and delete
Job Submission	<p>Print-ready files (PS, PCL, TIFF, PDF, XPS)</p> <p>Output feature selection</p>
Device Administration	Allows simple, remote installation setting of configuration options and management of the device
Browsers	<p>Windows® XP, 2000: Netscape Navigator®, Firefox®</p> <p>Microsoft® Internet Explorer</p> <p>Macintosh® 9.x/OS X: Netscape Navigator® 6.x, Apple® Safari™, Firefox®</p> <p>Linux: Netscape® 6.x</p>
EFI Fiery® Network Controller (Optional) – Available Post Launch	
Processor	1.86 GHz
Memory (ESS)	512 MB

WorkCentre 7425 / 7428 / 7435

System Disk	80 GB minimum
Print Languages (PDL)	PostScript 3
Features	<p>Command WorkStation capability via a PC or MAC (customer to provide) with Queue Management</p> <ul style="list-style-type: none"> • Job Preview • Job Merge • Change Job Properties <p>Pantone Colour Tables Expert Colour Settings: Profile, Rendering and Simulation ColorWise Pro Tools – calibration support, colour editor, profile manager FreeForm – Variable Data capabilities Booklet Maker 3.0 – booklet wizard to create booklets Print from USB flash drive Microsoft Office Doc conversion – print .doc, .xls, .ppt files without application</p>
Connectivity	Ethernet 10/100/1000BaseTX
Optional	<p>Hot folders and virtual printers Impose 2.7 – imposition Paper Catalog Spot On Colour Management Auto Trapping</p>

Fax Specifications

Network Fax Server Integration (Optional)

Fax Send Features	<p>One-sided, two-sided, or two-sided rotate side 2 Phone number entry Add to send list (50 numbers maximum) Delay send (specific time) Resolution selection (super fine/600 x 600, super fine/400 x 400, fine/200 x 200, standard/200 x 100 dpi) Original type (photo, text, or photo and text)</p>
Fax Print Features	<p>One- or two-sided printing Quantity Staple on/off Collate on/off Finisher output tray selection (top tray or main tray) Secure print on/off</p>
Fax Vendors	<p>Multiple vendors, certified by the Xerox Alliance Partner Programme For details, visit www.xerox.com</p>

Fax (Optional) – Standard with One or Three Line Fax Option

	<p>ITY (CCITT) group 3 quality/resolution superfine/600x600, super fine/400 x 400, fine/200x200, standard/200x100 dpi</p>
Speed/Modem(s)	V.34 modem(s): 33,600 bps. Less than four seconds per page transmission time. ISDN via third-party adapter.
Speed/Compression	MH/G3, MMR/G4, JBig Super G3
Fax Send Features	<p>Fax from print driver Auto fax transmission reduction Page-by-page job status at the machine Delay start Automatic memory resend Automatic cover sheets Priority send Broadcast Booklet Scan PSTN Fax Internet Fax LAN Fax</p>

WorkCentre 7425 / 7428 / 7435

Fax Receive Features	One- or two-sided printing Reduction at reception to fit available paper Junk Fax prevention
Fax Forward	When enabled with the scan and fax kit, faxes can be received into a folder on the device hard drive. Images that are in the folder can be routed to an Email, an FTP or SMB location or a Fax.
Fax Reports	Activity report Address Book Transmission confirmation Pending fax Folder List
Fax Receive Mailboxes	Up to 200 password-protected folders
Auto Dialing	Auto redial, Batch send
Single Line option	Total of 200 speed dials (single-line option) Up to 50 dial groups with up to 20 recipients per group (single line option) Up to 200 dial groups with up to 200 recipients per group (with extended memory option)
Internet Fax (Optional) – Standard with One or Three Line Fax Option	
Capability	Direct document transmission to remote Internet Fax machines or email clients (SMTP) Reception and automatic printout of documents in black and white sent via email from remote Internet Fax machines or email clients
Maximum Scan Area	A3
Address Directory Access	Downloaded address list (comma-separated value file format)
File Formats	TIFF-FX Profiles S with G3 MH, F with G4 MMR, or J with JBIG
Resolutions	600 x 600 dpi 400 x 400 dpi 200 x 200 dpi 200 x 100 dpi Bit Depth: 1 bit (black and white)
Network Protocols	SMTP POP3
Compliance	ITU-T T.37 compliant
Scan Specifications	
Scanning (Optional)	
Capability	Colour Scanning, Greyscale, Black and White, Auto Colour
Concurrency	Scan while the system is copying, printing or while it is transferring scan to network or fax jobs
Input Speed	Scan at 50 ipm black and white/45 ipm colour (210 x 297 mm/A4 long edge feed)
Resolution	600 x 600 dpi 400 x 400 dpi 300 x 300 dpi 200 x 200 dpi Bit depth: 1 bit (black and white), 8 bit (greyscale), 24 bit (colour)
Maximum Scan Area	297 x 432 mm
Secure Access and Authentication	Optional secure device login with network user name and password Supports: Kerberos (Windows 2000/UNIX/Windows Server 2003), SMB (Windows 2000/Windows Server 2003/Vista) LDAP

Network Protocol	FTP via TCP/IP Microsoft SMB via TCP/IP Netware, HTTP and HTTPS
File Formats	TIFF 6.0 or TTN2 with JPEG, G3MH, G4 MMR compression (single page or multiple pages) PDF, PDF/A with MRC, JPEG, G3 MH, G4 MMR, MRC, JBIG 2 Huffman, JBIG Arithmetic Compression JPEG XPS Searchable PDF, PDF/A, XPS Password Protected PDF Encrypted PDF Linearised PDF
Document Management Fields	One to six user-programmable metadata fields per scan job Customised fields viewed on user interface Variable data entered using virtual keyboard
Scan Features	Mixed size originals Bound originals Edge erase Reduction/enlargement Fit to size Scan Build Job Compression Quality/File Size Control Original type (photo and text, photo, text) Auto Background and Shadow Suppression Job Flow Sheets Thumbnail Preview
Supported Scan Destinations (Varies by scanning software options purchased.)	Scan to network server Scan to remote email destinations via direct SMTP addresses or via various network scanning software options Scan to application (Electronic Document Management System/Repositories) Scan to Microsoft Exchange 2000 Web Folders Scan to PC Desktop™ (Professional and SE editions) SMARTsend™ ScanFlowStore™ Scan to Windows XP client SMB or FTP Scan to Folder Scan to Home
Scan to PC Desktop SE	<ul style="list-style-type: none"> • A desktop and server-based offering that provides document imaging, archiving, editing and organisation tools • ScanSoft PaperPort – image viewing and file management software • ScanSoft OmniPage (for desktop/client installation) – OCR and file format conversion software • Image Retriever – provides fully automated retrieval of scanned images direct from a scan enabled Xerox WorkCentre to individual desktops.
Scan to PC Desktop Pro	<ul style="list-style-type: none"> • A desktop and server-based offering that provides document imaging, archiving, editing and organisation tools • The PaperPort Personal Scanning Platform empowers office workers with the ability to customise, directly from the desktop, the scanning menus available to them on Xerox EIP enabled MFP devices. • ScanSoft PaperPort Pro – image viewing and file management software • ScanSoft OmniPage Pro (for desktop/client installation) – OCR and file format conversion software • Image Retriever – provides fully automated retrieval of scanned images direct from a scan enabled Xerox or through email WorkCentre to individual desktops. Also includes an Email inbox polling capability.
Scan to Email (Included with the Scanning Option)	
Capability	Colour scanning, Auto Colour, Greyscale, Black and White Direct document email from device Manual or directory Exchange/Notes/LDAP address searching
Network Protocol	SMTP, S/MIME, LDAP, LDAPs encoded

WorkCentre 7425 / 7428 / 7435

Authentication	Device login with network user name and password Supports: Kerberos (UNIX/Windows 2003 Server), SMB, (Windows 2000/Windows 2003 Server) LDAP Domino		
Directory Access	Corporate address list via LDAPv3 Downloaded address list (comma-separated file format)		
Scan to Folder on the disk drive (Included with the Scanning Option)			
Capability	Colour, Auto Colour, Black and White		
Features	Images can be scanned, printed and faxed directly to the device hard drive and stored in a mailbox. Scan or fax images that are stored in the mailbox can then be printed, emailed, sent via fax, sent via IFax, routed to a PC, an FTP or SMB site via Job Flow Sheets.		
Thumbnail Preview (Optional)			
	Images that are stored in the folder on the device hard drive can be viewed at the User Interface.		
Device Specifications			
Security			
Capability	Secure Print, NDS Authentication over IP, LDAP/Kerberos/SMB, Password Protected PDF, Encrypted Disk, Audit Log and Encrypted Scan to Email. Hard disk overwrite immediate or on demand. Secure Web Page via SSL. IPv6		
Accounting			
Accounting with Third-Party Server Applications (optional)	Up-to-the-minute data on how the system is being used; comprehensive usage tracking and reporting; print, scan, copy and fax		
Auditron	Controls and tracks black and colour copy, print, fax and scan usage		
Accounting Control	Xerox Standard Accounting Job based accounting Third-party integration Supports Foreign Device Interface Active directory user profile – Controls colour copy and print usage Xerox Page Accountant Print Audit 5		
Accounting – Xerox Standard Accounting			
Tracking	Copy, Print, Fax and Scan usage		
Accounting	Up to 9,999 User accounts (User ID)		
Features	Enable/disable via the web UI or the GUI in tools, admin can manage the feature remotely via the web UI, Data can be exported via a CSV file, user required to enter XSA ID into the print driver when submitting a print job, similar to secure print.		
	WorkCentre 7425	WorkCentre 7428	WorkCentre 7435
Monthly Duty Cycle			
	60,000	80,000	105,000
Basic Configurations⁴			
	Network Multifunction System with network controller – Copy and Print capability standard		

⁴ Features, configurations and options may vary by location.

Accessories	
	<ul style="list-style-type: none"> Three Tray Module High Capacity Tandem Tray High Capacity Feeder Envelope Tray Integrated Office Finisher Office Finisher LX Booklet Maker (requires Office Finisher LX) Professional Finisher 2/4 Hole Punch (Office Finisher) 1500-sheet Professional Finisher with 50-sheet Stapling Swedish 4 Hole Punch (Professional Finisher only) Convenience Stapler Work Surface One-line fax with Internet Fax Three-line fax with Internet Fax Fax Server Enablement Thumbnail preview Foreign Device Interface Kit Secure Watermark Scan to PC Desktop (Professional or SE edition) Media Print (Print from a USB Thumb drive or media card) Parallel Port Printing Network Scanning Network Accounting Kit Security Kit Postscript Kit USB Media cable Kit USB Media Reader Kit Mobility Plate EFI Controller Secure Access SMARTSend
Electrical Requirements	
	220–240 V Nominal, 50/60 Hz, 10A
Power Consumption	
Running	< 646 watts
Standby	< 145 watts
Low-Power Mode	< 79 watts
Sleep Mode	< 2 watts
Warm Up	45 seconds (maximum)
Low-Power Recovery	30 seconds (maximum)
Required Temperature Range	10° to 28° C
Required Relative Humidity	15 % to 85 %
Noise Emission	20 dB(A) standby 56 dB(A) running
Heat Emission	2584 BTU/Hr running 580 BTU/Hr standby

WorkCentre 7425 / 7428 / 7435

Dimensions and Weights	Width	Depth	Height	Weight
Base Unit	1046 mm	678 mm	1125 mm	144 kg
Xerox Extensible Interface Platform™ (EIP)				
	Xerox EIP is a software platform inside the WorkCentre 7425/7428/7435 that enables personalised solutions you can access right from the device touch screen. These applications can leverage your existing databases and meet your specific business challenges.			
Certifications				
	EnergyStar 89/336/EEC (Europe) TUV Listed CB Certified (IEC 60950-1/EN 60950-1) 73/23/EEC (Europe) Novell Tested and Approved Windows Hardware Quality Labs			
Supplies	Description	Order Number		
Toner Cartridges	Black Toner Cartridge - Metered	006R01391		
	Yellow Toner Cartridge - Metered	006R01392		
	Magenta Toner Cartridge - Metered	006R01393		
	Cyan Toner Cartridge - Metered	006R01394		
Staple Refills	Integrated Office Finisher	008R12941		
	Office Finisher LX	008R12941		
	Professional Finisher	008R12941		
Staple Cartridges	Integrated Office Finisher	008R12964		
	Office Finisher LX	008R12964		
	Professional Finisher	008R12964		
	Booklet Maker for Office Finisher LX	008R12897		
	Booklet Maker for Professional Finisher	008R12925		
Smart Kits	Description	Order Number		
	SMart Kit™ Drum Cartridge	013R00647		
	SMart Kit™ Waste Cartridge	008R13061		
	SMart Kit™ Fuser Module (220 V)	008R13063		
	Intermediate Belt Transfer (IBT) Cleaner	001R00600		
	Belt Transfer Roller	008R13064		

